

Crypto M.2 SATA 6Gbps 22x60

**Full Disk Encryption
AES 256-bit**



128
GB

256
GB

512
GB

INTRODUCTION

The most secure next generation form factor encrypted SSD available.

If an ultrabook or laptop with an Integral Crypto M.2 SSD installed is lost or stolen, sensitive data is secure and cannot be accessed without the high-strength password. When the system is shut down, 256-bit full disk encryption is instigated.

Crypto M.2 SSD is the no-fuss and highly-secure solid state encryption solution for many industries including; finance, legal, health, education and government.

M.2 SATA SSD storage solutions are designed for Notebooks, Desktops, Ultrabooks and tablets. They address the need for more low powered compact storage without compromising performance and reliability of solid state drives.

FEATURES

- **Military level security with AES 256-bit hardware encryption** - More secure than a software-only solution.
- **FIPS 140-2 Validated** - Certificate No. 2126
- M.2 2260 form factor with SATA III 6Gbps interface (backwards compatible with SATA 3Gbps and SATA 1.5Gbps)
- Supports 'M' & 'B' Key sockets
- Performance: Faster boot than HDD, Faster access to applications, enhanced productivity and increased efficiency
- Fully compatible with devices and OS that support the SATA standard with M.2 M and B connectors
- **Multi-lingual interface** – in 14 languages*

Security Features

- **Total Drive Encryption** - All data stored on the Crypto M.2 SSD is encrypted (including the Operating System).
- **Dual Password** - As an option an Administrator can setup a user password and a master override password. If the user forgets their password, the Crypto M.2 SSD can be unlocked by the Administrator and the user password reset.
- **Secure Entry** - Encrypted data cannot be accessed without the correct high-strength 8-16 character alphanumeric password. An optional password hint can be set-up which cannot be the same as the password. Before use a high-strength password must be set.
- **Brute-Force Password Attack Protection** - Encrypted data is automatically erased after the default 6 failed password attempts (password attempts configurable to a maximum of 20). The data and encryption key are securely destroyed and the Crypto M.2 SSD is reset and can then be reused.
- **Anti-Clone** - Crypto M.2 SSD cannot be cloned once encryption is set.
- **Tamper-Proof Design** - The electronics are sealed in tamper-proof epoxy resin.
- **High-speed Read/Write** – The Crypto M.2 SSD has both high encryption and the main benefit of a performance SSD; a high-speed sustained data transfer rate.
- **Quick Boot** - Using a Crypto M.2 SSD in place of a traditional HDD can cut your ultrabook or laptop's boot time in half.
- **No moving parts** - greater resistance to shock and vibration
- **Noise free** - no spin or seek time
- **Endpoint security software compatible** – The Integral Crypto M.2 SSD operates comfortably with endpoint security solutions by using the configurable unique ID feature, which is part of the setup program
- **Warranty** – 3 Years

Technical Features

- MLC-NAND Flash Technology
- Compatible with Windows XP, Vista, 7 and 8

PERFORMANCE		
128GB	Read	450MB/s (up to)*
	Write	200MB/s (up to)*
256GB	Read	450MB/s (up to)*
	Write	350MB/s (up to)*
512GB	Read	450MB/s (up to)*
	Write	350MB/s (up to)*
INTERFACE		
Interface	SATA III 6Gbps Also Compatible with SATA II 3Gbps and SATA 1.5Gbps	
NAND	MLC	
Form Factor	M.2 22x60 'M' & 'B' Key connector	
Standard	M.2 (previously known as Next Generation Form Factor (NGFF))	
*Based on internal testing		
RELIABILITY		
MTTF	2,000,000 hours	
ECC algorithm	24 9-bit Symbols Correction per 512 9-bit Symbol	
POWER CONSUMPTION		
Supply Voltage	3.3V	
Power Consumption (mW)	Read : 128G = 1565 / 256G = 1630 / 512G = 1730	
	Write : 128G = 1620 / 256G = 1850 / 512G = 2250	
	Idle = 250	
Supports SMART Software	Yes	
Supports TRIM	Yes (OS support required)	
ECC algorithm	Supports 72bit ECC correct per 1K Byte	
MTBF	>1 Million Hours	
Compliance	CE, FCC, RoHS	
ENVIRONMENTAL		
Operating Temp	0° - +70°C	
Non - Operating Temp	-40° - +85°C	
Humidity	RH 90% under 40C in operation	
Vibration	80Hz~2000Hz / 20G	
PHYSICAL		
Length	60mm	
Width	22mm	
Height	3.8mm	
Weight	8g	
Length (Packed)	115mm	
Width (Packed)	132mm	
Height (Packed)	57mm	
Weight (Packed)	77g	
WARRANTY		
3 years		

APPROVED SECURITY FUNCTION	CERTIFICATE
AES (H/W implementation) • CBC (enc/dec; 256)	2175
XTS 128, XTS 256	2175
HMAC 512 HMAC 256	1335
DRBG	254
SHA 512 SHA 256	1887

*14 languages supported by the software GUI -

- Arabic
- Chinese
- Dutch
- English
- French
- German
- Hindi
- Italian
- Norwegian
- Polish
- Portuguese
- Russian
- Spanish
- Swedish

CAPACITY	PART CODE	BARCODE (EAN)
128GB	INSSD128GM2M2260C140	5055288428270
256GB	INSSD256GM2M2260C140	5055288428287
512GB	INSSD512GM2M2260C140	5055288428294

1GB = 1,000,000,000 bytes. Formatted capacity is less.

Please Note: No security software can be guaranteed 100% secure.

This device should not be used as your sole backup.

Product design and specification subject to change or modification without notice. E&OE.

All trademarks acknowledged.

For products with security software or hardware; the product cannot be guaranteed to be fully secure. No security system can be considered absolute.

For warranty information please visit www.integralmemory.com/warranty

